

Filtered MIL-DTL-83723 Connector Part Number Builder

W	F	O	W	1	4	-	0	7	P	S	N	C	B	5	-	4	7	3
WEMS Electronics MIL-DTL-83723 TYPE SERIES III THREADED F SERIES III BAYONET G MOUNTING STYLE SINGLE HOLE MOUNT 0 FLANGE MOUNT 1 SOLDER MOUNT 5 PLUG PUSH-PULL 3 PLUG 6 PLUG RFI 7 FINISH ELECTROLESS NICKEL F OD CAD W other finishes available, consult factory SHELL SIZE AND INSERT ARRANGEMENT (PER MIL-STD-1554) example: 14-07 CONTACT GENDER MALE PINS P FEMALE SOCKETS S CONTACT TERMINATION PC TAIL P SOLDER CUP S WIRE TERMINATION W CONNECTOR POLARIZATION N, 6-9, Y																		
CAPACITANCE (3 DIGIT) EXAMPLES: 221 220 pF 682 6,800 pF 473 47,000 pF VOLTAGE RATING (STEADY STATE) 0 50 VDC 1 100 VDC 2 200 VDC 3 300 VDC 4 400 VDC 5 500 VDC for values over 500, consult factory FILTER LOCATION S SHELL EXTENSION (AS REQUIRED) B BACKSHELL COMPATIBLE FILTER TYPE C CHIP CAPACITOR D DISCOIDAL / TUBULAR CAPACITOR P PI FILTER																		



Filtered MIL-DTL-26500 Connector Part Number Builder

W	H	1	A	1	4	-	0	7	P	S	N	C	B	5	-	4	7	3
WEMS Electronics MIL-DTL-26500 TYPE THREADED H BAYONET J MOUNTING STYLE SINGLE HOLE MOUNT 0 FLANGE MOUNT 1 SOLDER MOUNT 5 PLUG 6 FINISH ANODIC A CONDUCTIVE C other finishes available, consult factory SHELL SIZE AND INSERT ARRANGEMENT (PER MIL-STD-1554) example: 14-07 CONTACT GENDER MALE PINS P FEMALE SOCKETS S CONTACT TERMINATION PC TAIL P SOLDER CUP S WIRE TERMINATION W CONNECTOR POLARIZATION N, 6-9, Y																		
CAPACITANCE (3 DIGIT) EXAMPLES: 221 220 pF 682 6,800 pF 473 47,000 pF VOLTAGE RATING (STEADY STATE) 0 50 VDC 1 100 VDC 2 200 VDC 3 300 VDC 4 400 VDC 5 500 VDC for values over 500, consult factory FILTER LOCATION S SHELL EXTENSION (AS REQUIRED) B BACKSHELL COMPATIBLE FILTER TYPE C CHIP CAPACITOR D DISCOIDAL / TUBULAR CAPACITOR P PI FILTER																		

