

Filtered MIL-DTL-24308 Connector Part Number Builder

W	N	F	1	5	M	P	N	-	C	G	5	-	4	7	3
WEMS Electronics															
MIL-DTL-24308 TYPE															
STANDARD TYPE I N															
HIGH DENSITY TYPE II P															
FINISH															
ELECTROLESS NICKEL F															
OD CAD W															
other finishes available, consult factory															
PIN COUNT															
STANDARD TYPE I															
09, 15, 25, 37, 50															
HIGH DENSITY TYPE II															
15, 26, 44, 62, 78, 104															
CONTACT GENDER															
MALE PINS M															
FEMALE SOCKETS F															
MALE TO FEMALE ADAPTER MF															
CONTACT TERMINATION															
PC TAIL P															
SOLDER CUP S															
WIRE TERMINATION W															
IDC CONNECTOR D															
RIGHT ANGLE R															
OPTIONAL HARDWARE															
NO HARDWARE OR THREADED INSERT N															
THREADED INSERT T															
other options available, consult factory															
CAPACITANCE (3 DIGIT)															
EXAMPLES:															
221 220 pF															
682 6,800 pF															
473 47,000 pF															
VOLTAGE RATING (STEADY STATE)															
0 50 VDC															
1 100 VDC															
2 200 VDC															
3 300 VDC															
4 400 VDC															
5 500 VDC															
for values over 500, consult factory															
COMPLIANCE															
G STANDARD FILTER															
R RoHS COMPLIANT															
FILTER TYPE															
C CHIP CAPACITOR															
D DISCOIDAL / TUBULAR CAPACITOR															
P PI FILTER															

