

EMI Filter Connectors and Inserts



Filtered MIL-DTL-83513 Connector Part Number Builder

W R F 1 5 M P T - C G 5 - 4 7 3 WEMS Electronics MIL-DTL-83513 TYPE MICRO-D R FINISH ELECTROLESS NICKEL F OD CAD W other finishes available, consult factory PIN COUNT 9, 15, 21, 25, 31, 37, 51, 69, 100, 122 CONTACT GENDER MALE PINS M FEMALE SOCKETS F MALE TO FEMALE ADAPTER MF CONTACT TERMINATION PC TAIL P SOLDER CUP S WIRE TERMINATION W RIGHT ANGLE R OPTIONAL HARDWARE NO HARDWARE OR THREADED INSERT N JACKPOST P THREADED INSERT T JACKPOT AND THREADED INSERT W	CAPACITANCE (3 DIGIT) EXAMPLES: 221 220 pF 682 6,800 pF 473 47,000 pF VOLTAGE RATING (STEADY STATE) 0 50 VDC 1 100 VDC 2 200 VDC 3 300 VDC 4 400 VDC 5 500 VDC for values over 500, consult factory COMPLIANCE G STANDARD FILTER R RoHS COMPLIANT FILTER TYPE C CHIP CAPACITOR D DISCOIDAL / TUBULAR CAPACITOR P PI FILTER
---	--

